

# KEY18WA

18" ACTIVE  
SUBWOOFER – 1000 W

# KEY



The **KEY18WA** subwoofer is the ideal complement for enhancing bass response at any venue.

Best for a wider acoustic response at lower frequencies. Its helpful ergonomics makes transport easy and its high performance will give a nice tonal balance in any sound system.

**KEY18WA** opens the door to a convincing and accurate low end.

**KEY.** *Unlock the beat!*

## MAIN FEATURES

18" long excursion woofer with 4" voice coil.

Use alongside all models in the **KEY** series.

Built-in DSP with factory presets.

M20 top plate to use the cabinet with a rod.

Integrated and ergonomic recessed hand carry handles.

Optimized steel grille.

Multilayer plywood cabinet with matt black paint.

Light and compact.

El subwoofer **KEY18WA** es el complemento ideal para mejorar la respuesta de graves en cualquier lugar.

Ideal para ampliar la respuesta en las más bajas frecuencias. Su buena ergonomía facilita su transporte y su elevado rendimiento proporcionará un agradable equilibrio tonal en cualquier sistema de sonido.

**KEY18WA** abre la puerta a unos graves convincentes y precisos.

**KEY.** *Unlock the beat!*

## CARACTERÍSTICAS PRINCIPALES

Altavoz de 18" de alta excursión con bobina de 4".

Posible uso en combinación con el resto de modelos de la serie **KEY**.

Procesamiento mediante DSP que incorpora presets de fábrica.

Pletina de M20 en la parte superior para utilización con barra soporte.

Asas de transporte integradas.

Optimizada reja protectora de acero.

Tablero multicapa y acabados en pintura mate negra.

Ligero y compacto.

# KEY18WA

18" ACTIVE  
SUBWOOFER – 1000 W

# KEY



VIEW WITHOUT GRILLE




REAR VIEW

## TECHNICAL FEATURES


## KEY18WA

Amplifier	1000 W
Input sensitivity	2 dBu
Input Impedance	20 k $\Omega$
Maximum input level	20 dBu
Mains	Universal Switch Mode Power Supply 85-265 V / 45-65 Hz
Average current draw (Heavy duty musical program)	1 A
Standby Mode Consumption	< 5 W
SPL (1 m)	127 dB continuous, 130 dB peak
Built-in DSP	48 bit
Built-in delay line	118 ms / 40 m
AD/DA converters	24 bit – 48 kHz
Frequency response (-10 dB)	34 Hz – 90/100/110 Hz
Components LF	18" woofer (4" voice coil)
Directivity (HxV)	Omnidirectional
Dimensions (HxWxD)	700 x 550 x 605 mm
Weight	41.9 kg
Finish	Multilayer plywood Front steel grille with foam Black matt ecological paint


## ACCESSORIES



FC-KEY18W



NC-KEY18W



SP/CR