



The VO-4 is a networked audio output expansion device allowing the user to add four line-level output channels to a Vocia® system. The VO-4 accepts four channels of digital audio input via CobraNet® and provides four line-level analog audio outputs. The VO-4 features embedded DSP and on-board memory to process and store all device-specific configuration information locally and includes comprehensive fixed-chain digital-signal processing. As part of the Vocia system, the VO-4 meets paging requirements for facilities of all sizes.

FEATURES

- Converts digital to analog
- Four removable terminal block connectors for line-level outputs
- Four control inputs and four control outputs
- Software-configurable local audio signal processing, including gain, filters, and compressor/limiter
- Rotary switches for unit identification
- Power Over Ethernet (PoE)
- CobraNet audio/control with dynamic use of available bundles, plus power over single Ethernet cable
- Status LEDs to indicate signal and clip
- **CE** marked, **UL** listed and **RoHS** compliant
- Covered by Biamp Systems' warranty

ARCHITECTS & ENGINEERS SPECIFICATION


The audio output device shall be designed exclusively for use with Biamp® Vocia systems. It shall be rack mountable (1RU) and provide audio and control via CobraNet®. It shall receive Power over Ethernet (PoE) utilizing a single (CAT5) network cable to a rear panel RJ45 connector. The output device shall provide four removable terminal block connectors for line-level audio outputs, four control inputs, and four control outputs. The audio output device shall provide local digital audio signal processing and local storage of configuration data. The audio output device shall indicate signal and clip with LEDs on the front panel. The audio output device shall be CE marked, UL listed and shall be compliant with the RoHS directive. Warranty shall be five years.

The output device shall be a Vocia VO-4.

Vocia Output 4 SPECIFICATIONS

Frequency Response:	20Hz to 20kHz + or - 1dB	Control Outputs:	Type: Form C Voltage free change over contact
THD + N (20Hz to 8kHz):	<0.02%	Max Operating Voltage:	125VAC, 60VDC
Dynamic Range:	>100dB	Max Switching Capacity:	37VA
Crosstalk (10kHz):	>80dB	Min Operating Load:	10µA @ 10mV DC
Minimum Load Impedance:	600kΩ	Connection:	RJ45 with shielded Ethernet/PoE cable (CAT5, CAT5e, CAT6, or CAT7)
Maximum Output Level:	>+22dBu	Power:	802.3af (PoE) Class 3
Nominal Output Level:	-10dBu, 0dBu, or +4dBu	Dimensions:	Height: 0.75 inches (44.5mm) Width: 19 inches (483mm) Depth: 10 inches (254mm)
A/D Converters:	24-bit (48kHz sampling)	Weight:	6.4 lbs. (2.9kg)
Control Inputs	Type: Digital, variable threshold	Ambient Operating Temperature Range:	32-113 degrees F (0-45 degrees C)
Max Input Threshold:	10V	Compliance:	EU Directive 2002/95/EC RoHS Directive CE marked EN 60849, AS 60849 verified
Max Input Voltage:	12V		
Min Input Threshold:	150mV		
Input Impedance:	100kΩ		

Vocia Output 4 BACK PANEL



Vocia Output 4 BLOCK DIAGRAM

