



# kramer

## WP-SW2-EN7

4K AVoIP Encoder Switcher Wall Plate

---

US

EU / UK



WP-SW2-EN7 is an advanced wall plate encoder for streaming 4K video signals via Ethernet over copper cable

## FEATURES

---

**Video Streaming Transmitter** - Streams up to 4K@60Hz (4:2:0) resolution signals over a 1G network interface

**Streaming Support** - Unicast and multicast

**Multiple Inputs** - One HDMI input and one USB-C input, which support multiple switching policy including Last connected, Priority and Manually

**Analog Audio Embedding** - Embed the unbalanced analog audio into the streaming and HDMI output signal

**Convenient and Comprehensive Control** - Control the unit using intuitive web interface, protocol 3000 API commands via Ethernet, or front panel LCD and navigation buttons

**Control Gateway** - Through P3K or special TCP connection, user can control/communicate with RS232, CEC to the connected devices

**PoE Support** - Option to power with PoE connection from a PoE switch




# kramer

## TECHNICAL SPECIFICATIONS

---

Inputs	1 HDMI On a female HDMI connector 1 USB On a USB-C connector 1 Audio On a female 3.5mm mini jack
Ports	2 Ethernet On RJ-45 female connectors 1 RS-232 On a 3-pin terminal block connector
Network	Multicast Through RTSP (Real Time Streaming Protocol): IGMP snooping non-blocking, Layer 2  Unicast Through RTSP (Real Time Streaming Protocol)  Bitrate Peak: 850Mbps, 4K average: 350Mbps, 1080p average: 250Mbps
Video	Compression Standard JPEG based, private stream  Max Resolution 4K@30Hz 4:4:4
Video Streaming	Compression Standard: JPEG2K based, proprietary stream  Max Input Resolution: 4K@60hz (4:2:0)  Max Output Resolution: 4K@30hz (4:4:4)  Max End-to-End Resolution: 4K@30hz (4:4:4)  Scaler: Yes  End-to-End Latency: 33msec  Switching Time: 1sec
Resolution	4096x2160@60Hz, 1600x1200@60Hz, 1280x960@60Hz, 848x480@60Hz, 3840x2160@60Hz, 1600x900@60Hz, 1280x800@60Hz, 800x600@60Hz, 1920x1200@50Hz, 1440x900@60Hz, 1280x768@60Hz, 720x576@60Hz, 1920x1080@60Hz, 1400x1050@60Hz, 1280x720@60Hz, 720x480@50Hz, 1856x1392@60Hz, 1366x768@60Hz, 1224x768@70Hz, 640x480@60Hz, 1792x1344@60Hz, 1360x768@60Hz, 1152x864@70Hz, 640x400@85Hz, 1680x1050@60Hz, 1024x768@60Hz, 640x350@85Hz
Audio	Supported Formats LPCM, Dolby and DTS  LPCM LPCM upto 7.1/24-bit/192kHz  Dolby Dolby Atmos, Dolby TrueHD, Dolby Digital Plus, Dolby Digital EX, Dolby Digital 5.1, Dolby Digital 2/0 Surround, Dolby Digital 2/0  DTS DTS-HD Master Audio, DTS-HD, DTS-ES Discrete 6.1, DTS-ES Matrix 6.1, DTS Digital Surround 5.1
Security	HTTPS, 802.1x, OWASP-10
User Interface	Indicators HDMI, USB and ON LEDs, front panel channel display  Recessed Buttons CH+, CH- and factory reset button
Power	PoE (Power over Ethernet): 37V to 57V, maximum power consumption 12W  Optional Power Supply: 20V DC, 6A Max  Consumption when using Optional Power Supply: 68W (with USB-C charging)

Environmental Conditions	Operating Temperature 0° to +45°C (32° to 113°F)
	Storage Temperature -20° to +70°C (-4° to 158°F)
	Humidity 10% to 90%, RHL non-condensing
Regulatory Compliance (Standards Compliance)	Safety CE, FCC
	Environmental RoHs, WEEE
Enclosure	Size 2 Gang
	Type SGCC (galvanized steel) and PC (polycarbonate)
	Cooling Convection Ventilation
Product Dimensions	US: 12.10cm x 4.56cm x 12.10cm (4.76" x 1.80" x 4.76" ) W, D, H
	UK: 15.10cm x 4.00cm x 8.60cm (5.94" x 1.57" x 3.39" ) W, D, H
Product Weight	US: 0.4kg (1.0lbs) approx
	UK: 0.4kg (0.9lbs) approx
Shipping Dimensions	US: 20.00cm x 13.70cm x 7.50cm (7.87" x 5.39" x 2.95" ) W, D, H
	UK: 23.80cm x 13.70cm x 7.50cm (9.37" x 5.39" x 2.95" ) W, D, H
Shipping Weight	US: 0.7kg (1.5lbs) approx
	UK: 0.7kg (1.4lbs) approx



CONFIGURATIONS

WP-SW2-EN7/US-D(W) High-performance, highly scalable, AVoIP Wall Plate Encoder for 4K60 4:2:0, HDR10 over 1G Network, with white Decora® Design Frame Sets

WP-SW2-EN7/EU-D(W)80/86 80/86(W) High-performance, highly scalable, AVoIP Wall Plate Encoder for 4K60 4:2:0, HDR10 over 1G Network, with EU & UK White Frames

