

KRAMER NETWORK 1.0 Specifications

This document describes the **KRAMER NETWORK** 1.0 Specifications. For information about server requirements, see *Kramer Network Installation Prerequisites*, available at www.kramerav.com/support/product_downloads.asp?pid=3279

Client Operation System

- Google Chrome
- Mozilla Firefox
- Microsoft Internet Explore
- Microsoft Windows 10 Edge

Network

- Kramer Network scan devices and auto-detect on LAN or on a single VLAN
- The requirement for the network is L2 IP switching
- For streaming the network should support Multicast

Concurrent Clients

- Up to 10 concurrent clients (logged in users) recommended

Streaming

- KDS-EN3 H.264 encoder, KDS-DEC3 H.264 decoder
- FC-404 NET, Dante streamer
- Up to 100 streaming devices

Pro-AV Kramer Devices

- Kramer Pro-AV devices that support p3K, auto-detection and launch Web-interface – practically unlimited

IP Devices

- IP devices, manually added, launch Web-interface - practically unlimited

Control

- Virtual server, based on K-Config 3.0
- Up to 100 controlled devices or 10 rooms recommended

Users

- Super User: single
- Admin level: practically unlimited
- User level: practically unlimited

User Levels

- Built-in three levels, with fine-tune option in two of them