


BM 3003 3 ZONE PAGING MICROPHONE


Description	The BM 3003 paging microphone allows to make selective calls to 3 zones the RCF ES 3323 mixer amplifier (with tuner and CD/USB-MP3 player insid The inputs 2 and 3 of the RCF ES 3323 amplifier have a RJ 45 port (each) t microphone quickly and directly (through CAT 5 cable) or a line made of m microphones by using 1 or more additional power supply units.	e). o connect a BM 3003 paging		
Features	 Plastic body with 300 mm gooseneck PTT button with LED, Zone buttons with LED Power supplied by 'Phantom' (18 ÷ 48 V dc) for the BM 3003 directly con It can be directly connected to ES 3323 amplifiers External power supply AC AD2405 to be used on all BM 3003 connect to Lines of max. 12 BM 3003 paging microphones Polyurethane foam wind screen 5 m connecting cable (with RJ 45 plugs) included 			
Part Number	r 14322012 BM 3003 Grey	EAN 8024530006617		




BM 3003 3 ZONE PAGING MICROPHONE

Line Art 2D







	TECHNICAL SPECIFICATIONS	
Microphone specifications	Туре	Desktop paging microphone with electret capsule
	Directivity	Cardioid
	Sensitivity	-65 dB
	Frequency Response (-3dB)	50 Hz ÷ 18 kHz
	Minimum load impedance (ohm)	470.00 ohm
	Nominal output voltage @3.3 kohm (mV RMS)	100.00 mV RMS
Console specifications	Console Type	Paging
	General call	Yes
	Selective call	Yes
	Number of zones	3
	LED indicators	Yes
Power requirement	Power consumption	2.80 mA
Connections	Connectors	RJ45
Functionalities	Smart PTT	Yes
Accessories	Cable included	Yes
	Cable length (m)	5
Standard compliance	Safety agency	CE compliant
Physical specifications	Cabinet/Case Material	Plastic
	Color	Grey
Size	Height	48 mm / 1.89 inches
	Width	100 mm / 3.94 inches
	Depth	159 mm / 6.26 inches
	Weight	0.73 kg / 1.61 lbs