

MC 4064

UNIVERSAL HIGH QUALITY MICROPHONE

DESCRIPTION

MC 4064 is a slim cardioid electret microphone having a flexible gooseneck. It offers impressive acoustic features and a mechanical design that is ideal for public address sound systems. This microphone has two switches (PUSH, LOCK), a red ring lamp that lights up when the microphone is activated, a high-pass filter with a switch to cut frequencies below 100 Hz. It can be mounted on tables (with or without a hole), podiums, pulpits, etc.. It can be mounted on microphone floor stands too. It has a built-in 'Phantom' power circuit; therefore, it needs to be connected to a mixer microphone input with 12 V ÷ 52 V 'Phantom' power supply.



FEATURES

- Double joint gooseneck, 670 mm long
- Installation on desks (with or without hole), lecterns, mic. floor stands
- Buttons for stable and unstable microphone activation.
- Red ring for active microphone indication.
- High-pass filter with a switch to cut frequencies below 100 Hz.
- Phantom power supply (12 ÷ 52 V)
- 3m shielded and balanced cable with XLR connectors and 2 additional wires for command
- Polyurethane foam windscreen

TECHNICAL SPECIFICATIONS**Microphone specifications**

Type:	Electret
Directivity:	Cardioid
Sensitivity:	-48 dB
Frequency Response (-3dB):	100 Hz ÷ 12 kHz
Output impedance (ohm):	60.00 ohm
Phantom power:	Yes
Phantom Power:	12 V DC - 52 V DC

Connections

Connectors:	XLR
-------------	-----

Accessories

Cable included:	Yes
Cable length (m):	3

Standard compliance

CE marking:	Yes
-------------	-----

Physical specifications

Cabinet/Case Material:	Metal
Color:	Black

Size

Height:	662 mm / 26.06 inches
Diameter:	21 mm / 0.83 inches

Shipping informations

Package Height:	70 mm / 2.76 inches
Package Width:	510 mm / 20.08 inches
Package Depth:	130 mm / 5.12 inches
Package Weight:	0.26 kg / 0.57 lbs

PART NUMBER

- **14115025**

MC 4064

EAN 8024530012014