

## TTL 33-A II WP STADIUM

### ACTIVE THREE-WAY LINE ARRAY MODULE



#### Description

The TTL 33-A II WP STADIUM is a full range, ultra-compact, wide dispersion line array module that sets a new standard in the TT+ Stadia sound reinforcement, offering substantial power and efficiency for a variety of professional outdoor applications, including stadia, sports arenas, concert halls and other fixed venue installations.

Loudspeakers are strenghtened with a special waterproof film and a multi-layer coating on the grille, that is highly resistant to humidity, but transparent to sound.

#### Features

- > Effective 1250W switching power supply
- > 6 high-power neodymium transducers
- > Weatherproof touring-grade Baltic birch cabinet
- > RDNet compatible
- > IP 67 connectors
- > Lightweight anti-hygroscopic resin on transducers
- > Amplifier, DSP and connections protected against humidity
- > Safe rigging and hanging
- > Real-time monitoring and control exceeding EN60849 requirements
- > Front-grille designed for outdoor applications

#### Part Number

TTL 33-A II WP 13000402 STADIUM

220-240 V Black

EAN 8024530010577



# TTL 33-A II WP STADIUM

### ACTIVE THREE-WAY LINE ARRAY MODULE

**TECHNICAL SPECIFICATIONS** 

**Acoustical specifications** Frequency Response 60 Hz ÷ 20000 Hz

Max SPL @ 1m 135 dB 100° Horizontal coverage angle 15° Vertical coverage angle

**Transducers** Compression Driver 3 x 1.0" neo, 1.5" v.c

Midrange 1 x 8" neo, 2.0" v.c Woofer 2 x 8" neo, 2.5" v.c

Input/Output section Input signal bal/unbal

XLR, RDNet Ethercon Input connectors Output connectors XLR, RDNet Ethercon -2 dBu/+4 dBu Input sensitivity Crossover Frequencies 400 Hz - 1800 Hz

**Processor section** 

Thermal, HF Protections Limiter Fast Limiter

Controls HF Correction, cluster size, HPF

**RDNet** Onboard

Power section **Total Power** 2500 W Peak, 1250 W RMS

High frequencies 500 W Peak, 250 W RMS Mid frequencies 1000 W Peak, 500 W RMS Low frequencies 1000 W Peak, 500 W RMS Convection/Forced Cooling Connections Powercon IN/OUT

Standard compliance CE compliant Safety agency

**Physical specifications** Cabinet/Case Material Baltic birch plywood

> Hardware Array side fittings screws (8 per side rear)

Grille Steel Color Black

Size / Weight 300 mm / 11.81 inches Height

> Width 760 mm / 29.92 inches Depth 450 mm / 17.72 inches 33 kg / 72.75 lbs Weight

**ACCESSORIES** 

Cables **CABLES KIT** 13360102 AC XLR 3M3F EAN 8024530006402

**Technical Specifications** Page 2 of 2