

SA-60Q/SA-120Q/SA-180Q/SA-240Q

Mixer Amplifier With MP3, Bluetooth, Radio And Display



Features

- 1. Built-in MP3 player, MP3 and WMA dual decoding, USB interface, super disk reading capability.
- 2. Support MP3, WMA, WAV and other song formats.
- 3. Bluetooth function, which can be connected to the mobile phone Bluetooth to play the music in the mobile phone.
- 4. MP3 can be set to four playback modes: random, single loop, folder loop and all loop.
- 5. Radio function, built-in FM tuner.
- 6. New 128 * 64 graphic dot matrix display. The display content is rich and clear.
- 7. 5 sound effects optional, adapt to the hearing habits of people at different levels.
- 8. The name, length and playing time of Chinese and English songs can be displayed.
- 9. Dynamic spectrum display, more dynamic design.
- 10. With bell prompt and alarm functions.
- 11. 2 microphone inputs, 3 line inputs, 1 line output.
- 12. Microphone 1 has priority (automatic mute function).
- 13. Indication of power supply, signal and peak clipping.
- 14. Separate volume control for microphone and line input, total volume control.
- 15. 70V, 100V constant voltage output, 8 ohm constant resistance output.
- 16. Treble and bass tone control.
- 17. Infrared remote control function, all operations can be operated remotely.
- 18. Perfect output short circuit protection and over-temperature, over-voltage, over-current, anti-DC output midpoint protection.

Technical parameters

Model	SA-60Q	SA-120Q	SA-180Q	SA-240Q
Rated output power	60W	120W	180W	240W
Power consumption	120W	180W	270W	360W

30



Speaker output	70V, 100V & 4~16Ω						
Line out	600Ω/1000mv(0db)						
Input	MIC1,2/600 Ω , 2.0 MV (-54db), unbalanced; AUX1,2/10K Ω , 250 MV (-10						
	db), unbalanced						
Frequency	20HZ~20KHZ						
response							
Harmonic	 ≤0.1%@1KHZ						
distortion	<u>-</u>						
Signal to noise	>75db						
ratio							
Tone adjustment	Bass±10dbat100HZTreble: ±10dbat10KHZ						
Protect	Startup protection, over-voltage protection, DC protection, short-circuit						
	protection and over-temperature protection						
Mute	MIC 1, bell, alarm sound						
Operating							
temperature/hu	-20℃~+60℃/10%~90%						
midity							
Power supply	AC220V/50HZ						
Size	482×310×70 (mm)						
Weight	6.3Kg	7Kg	8.1Kg	9.6Kg			